

M A T E R I A L S A F E T Y D A T A S H E E T

I. P R O D U C T I D E N T I F I C A T I O N:

Prepared by: Visual Pollution Technologies, Inc. P.O. Box 12833, Scottsdale, AZ 85267
Info Phone:480-657-9183 Chem Emergency 800-255-3924 Prepared 4/14/97 By T.W.Smoot

Product Name: Crystal Clear Product Code: CC

II. H A Z A R D O U S I N G R E D I E N T S:

	Percent	CAS.#	OSHA/TWA	ACGIH TLV
Homopolymer of HDI	50-75%	28182-81-2	NE	NE
Aromatic Petroleum Distillates	< 15%	64742-94-5	NE	NE
Propylene Glycol Monomethyl Ether Acetate	< 25%	108-65-6	NE	NE

III. H E A L T H H A Z A R D I N F O R M A T I O N:

Routes Of Entry: Inhalation Ingestion Skin Eyes
Effects of Over Exposure: EYE CONTACT: can cause damage, if not rinsed quickly.
SKIN CONTACT: can cause allergic skin reaction
INHALATION: can cause lung damage. Can aggravate respiratory disorders.
INGESTION: can cause gastrointestinal irritation.
HMIS HAZARD INDEX:

HEALTH - 2
FLAMMABILITY - 2
REACTIVITY - 0

IV. E M E R G E N C Y F I R S T A I D:

INGESTION: Get medical help at once.
INHALATION: Remove to fresh air. If continued difficulty, get medical attention.
EYE CONTACT: Flush with water for at least 15 minutes, get medical help if irritation persists. DO NOT RUB EYES.
SKIN: Wash well with soap & water.

V. F I R E & E X P L O S I O N D A T A:

Flash Point: > 114°F Test Methods: T.C.C.
Flammability Limits In Air, % by Vol.: ND Lower: ND Upper
Extinguishing Media: alcohol foam, water fog, carbon dioxide, dry chemical.
Special Fire Fighting Procedures: Treat as flammable material.HDI vapors and other gases may be generated during fire.
Unusual Fire Fighting Hazard: Vapors are heavier than air and may travel and be ignited by heat.

VI. A C C I D E N T A L R E L E A S E M E A S U R E S:

Remove ignition sources; ventilate area. Dam up and neutralize with weak alkaline materials. Treat as flammable liquid.

VII. H A N D L I N G & S T O R A G E:

Keep container closed when not in use. Store in ventilated area, away from source of flame or sparks. Ideal storage temperature is between 50-81°F.

VIII. E X P O S U R E C O N T R O L / P R O T E C T I O N:

For extended usage, wear chemically resistant gloves; work in well ventilated area; eye protection is recommended. For spray applications use a respirator approved for use with isocyanate.

IX. P H Y S I C A L D A T A:

Boiling Point: ND
Specific Gravity,(HOH=1):1.0 ph,1% Sol.: ND
Vapor Pres.: MMHg@20C ND Solubility: Negligible.
Vapor Density(Air=1): ND Evaporation Rate: NA
VOC: Less than 2.8 lb/gal
Description/odor: Clear, pale yellow liquid. Slight aromatic.

X. S T A B I L I T Y A N D R E A C T I V I T Y:

Product is stable. ; Hazardous Polymerization: will not occur ; Conditions to avoid: NA

XI. T O X I C O L O G I C A L I N F O R M A T I O N:

Not listed by NTP, IARC, or regulated by OSHA as carcinogenic.

XII. E C O L O G I C A L I N F O R M A T I O N:

Not determined but do not allow to go to public water.

XIII. D I S P O S A L I N F O R M A T I O N:

Treat as flammable material: Dispose of according to Local, State & Federal Regulations.

XIV. T R A N S P O R T I N F O R M A T I O N:

DOT HAZARD CLASSIFICATION: 40 CFR 172.101.Paint Related Material,3,UN1263, III

XV. R E G U L A T O R Y I N F O R M A T I O N:

CERCLA RQ -40 CFR 302.4: NONE
SARA TITLE III: SECTION 302 Extremely hazardous substances: 40CFR 355 Appendix A:NONE
Section 311/312 Hazard Categories: Immediate health hazard; Fire hazard.
Section 313 Toxic Chemicals: NONE

RCRA status: This product is not listed as a hazardous waste. However, under RCRA, it is the responsibility of the product user to determine, at the time of disposal, whether a product meets any of the criteria of a hazardous waste. 40CFR261.20-

XVI. A D D I T I O N A L I N F O R M A T I O N: NA

The information contained herein is based on data available to us and is believed to be correct. We make no warranty, however, expressed or implied regarding the accuracy of these data or the results obtained from the use thereof.