



NOFUNG

ACRYLIC SEALER WITH ANTI-MOLD INHIBITORS

TECHNICAL DATA SHEET

GENERAL INFORMATION

NOFUNG is an exclusive formulation that seals interior and exterior concrete surfaces. **NOFUNG** is a ready to use acrylic emulsion with no hazardous components or odors. It will protect new and old concrete from dusting or oil penetration. **NOFUNG** is effective on natural porous and non-porous surfaces, brick, tile, concrete, stucco, wood, stone, metals, granite, precast concrete, exposed aggregate, split face block, etc. It can be used on walls, floors, signs, statues, sculptures.

NOFUNG works as a barrier between the elements and the underlying surface.

NOFUNG contains special inhibitors that prevent the formation and growth of mold, mildew and algae spores.

NOFUNG is a clear sealer that is formulated to provide durable, long lasting protection.

ADVANTAGES

- ** One Step Application
- ** No Thinning or Mixing
- ** Single coat application
- ** Non yellowing
- ** Non hazardous
- ** No obnoxious odors
- ** Moisture prevention
- ** Vapor Barrier
- ** Fast Drying-dries and protects in 24 hours.
- ** RETARDS THE GROWTH OF MOLD, MILDEW & ALGAE

DIRECTIONS FOR USE

For newly poured concrete surfaces, curing must be complete before application. Best results are obtained when the surface has been neutralized with a mild acid wash before application. When neutralization has been achieved and the surface is dry and cured, apply sealer evenly. Depending upon surface characteristics, application may be made by mopping, spraying, brushing or rolling.

COVERAGES (sq. ft. per gallon)

Depending upon surface preparation and application technique.

** Precast concrete.	200-400.
** Porous masonry, exposed aggregate, concrete, brick, block.	200-320

APPLICATION:

NOFUNG may be applied to most vertical or horizontal surfaces, including, but not limited to, brick, tile, stone, block, split face block, stucco, concrete, marble, granite, wood, metal. See MSDS for suggested protective gear. It is recommended to use all safety precautions when using any product.

VPT,LLC VISUAL POLLUTION TECH P.O. BOX 12833 * SCOTTSDALE, AZ 85267

Tel: 480-657-9183 * Fax: 480-767-2796 * Toll Free: 888-887-8347 Email: vispol@Aol.com

"Eye on solutions to tomorrow's problems...Today."