



MELT DOWN

ELIMINATES STYROFOAM FROM CONSTRUCTION SITES AND LAND FILLS TECHNICAL DATA SHEET

DESCRIPTION

MELT DOWN contains no petroleum distillates, organic halides or any other hazardous ingredients or unsafe chemicals according to OSHA Regulations (24 CFR, SEC 1900, 1200).

MELT DOWN eliminates Styrofoam, EPS, and other related products from CONSTRUCTION SITES and land fills by decomposition. It safely makes them "disappear". Eliminates the space required to bury the products that are manufactured with Styrofoam, which does not decompose. It accomplishes this without generating noxious fumes. One gallon of **MELT DOWN** will decompose approximately 200 s.f. of 2" thick foam.

MELT DOWN is biodegradable, non corrosive and safe to work with.

ADVANTAGES

- * No Harmful or Hazardous Ingredients
- * Non-Toxic
- * Non-Fuming
- * Non-Acid
- * Biodegradable
- * Simple spray application
- * Pleasant Aroma
- * Environmentally Friendly

FOR USE BY

- * Construction Contractors
- * Municipalities
- * Solid Waste Management
- * Disposal Companies
- * Styrofoam Manufacturers
- * Restaurants
- * Fast Food Locations
- * Supermarkets & Groceries

VPT VISUAL POLLUTION TECHNOLOGIES, INC. P.O. BOX 12833 * SCOTTSDALE, AZ 85267

Tel: 480-657-9183 * Fax: 480-767-2796 * Toll Free: 888-887-8347 Email: vispol@aol.com

"Eye on solutions to tomorrow's problems... Today."